

9390

Western States Asphalt**STRAIGHT BILL OF LADING**

In Emergency call Chemtrec at 800-424-9300 and
Reference ERG for Emergency Response
Information, for Chemtrec ID # 612045.

This is to certify that the below named materials are properly classified, described, packaged, marked, and labeled, and are in proper condition for transportation according to the applicable regulations of the Department of Transportation.

Signature By

Jeff D. Kurth

Cargo Tank Supplied By Carrier/Carrier Compliance to Laws - Where the cargo tank is supplied by the carrier, the carrier hereby certifies that the cargo tank supplied for this shipment is a proper container for the transportation of this commodity. This is to acknowledge that the carrier has in his possession or has been offered and accepted the required hazard materials placards and/or emergency response information.

The property described herein in apparent good order is received by the carrier shown on this Bill of Lading and the carrier agrees to transport the property to the consignee and the destination set forth herein subject to the classifications and tariffs, and the terms and conditions of the Uniform Domestic Straight Bill of Lading found in National Motor Freight Classification, in effect on the date of issuance of this Bill of Lading or the applicable contract with shipper. It is further agreed by the carrier that the transportation of this shipment will be performed in compliance with all applicable rules, regulations and laws.

Signature of Motor Carrier

Jeff D. Kurth

ORIGIN 3152 Selph Landing Road Pasco WA 99301	SHIPPER Western States Asphalt, LLC	CARRIER Columbia Asphalt & Gravel Inc
SOLD TO Columbia Asphalt & Gravel Inc	CONSIGNEE/DESTINATION Wapato	
BILL OF LADING WA-175471	SHIP DATE 08/08/2019	

FOB: Origin

Time In:

Agreement: WA-6046

Freight: Collect

Time Out: 12:05PM PT

Customer PO#:

Time Due:

Refiner: Exxon, Cenex, Calumet, Husky,
Imperial, US Oil, Centennial Energy

Loaded By: Kurth, Jeff

Tank #: 12

Truck #: 52-111090

Trailer #: 97-a

Contract #: Commercial CSS

PRODUCT/ALIAS	TEMP	GROSS VOL	NET VOL	WEIGHTS	
CSS-1	145F	4,759.29 GAL	4,658.16 GAL	GROSS: 75,520 LBS	34,255.30 KG
	63C	1,257.27 MT	17,633.05 LT	TARE: 35,880 LBS	16,274.89 KG
				NET: 39,640 LBS	17,980.40 KG
				19.82 TON	17.98 MT

Number of Units & Container Type: Cargo Tank

Proper Shipping Description

NR. This product is not regulated as a hazardous material by the US DOT.

Pounds per Gallon: 8.510

Kilograms per Liter: 1.020

Specific Gravity @ 60F 1.0197

When an agency requires a quality control plan, Western States Asphalt, LLC certifies the material provided under the Bill of Lading meets the requirements of the plan provided to the agency. Weights per Gallon and Specific Gravities noted are typical and can vary through manufacturing and handling.

Authorized Signature:

Jeff D. Kurth

Internal Control # 726000002506

To request a current SDS in non-emergency situations, please call 509-487-4560

FOR ADDITIONAL INFORMATION, SEE PRODUCT'S SAFETY DATA SHEET - EMERGENCY ASSISTANCE CALL CHEMTREC 800-424-9300

WARNING!! HEATED MATERIAL MAY CAUSE THERMAL BURNS. MAY BE SEVERELY IRRITATING TO EYES, SKIN, AND RESPIRATORY TRACT. MAY RELEASE TOXIC HYDROGEN SULFIDE VAPOR. DO NOT RELY ON ODOR FOR WARNING. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. MAY CAUSE ALLERGIC REACTION IN SOME INDIVIDUALS. MAY CONTAIN MATERIAL WHICH MAY CAUSE CANCER AND/OR REPRODUCTIVE HAZARD. LIQUID AND VAPOR MAY BE FLAMMABLE. MAY BE HARMFUL IF ABSORBED THROUGH THE SKIN. Keep away from heat, sparks, or flame. Keep container closed. Use only with adequate ventilation. Do not eat, drink, or smoke in areas of use or storage. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. **FIRST AID:** For skin contact with hot material, flush skin with large amounts of cold water - cover with gauze. DO NOT try to remove solidified material from the skin. DO NOT try to dissolve with solvents or thinners. For cold material, immediately wash skin with plenty of soap and water. In case of contact with eyes, flush with large amounts of water while holding eyelids open. Burns due to contact with heated material require immediate medical attention. If inhaled, safely remove the victim to fresh air. If not breathing, institute rescue breathing. If breathing is difficult, clear airways and give oxygen. If swallowed, get immediate medical attention. Do not induce vomiting. In case of fire, use dry chemical, alcohol foam, all purpose AFFF or carbon dioxide to extinguish fire. Exercise extreme care when using water spray on asphalt tank fires. Ground lines and equipment used during transfer to reduce the possibility of static spark-ignited fire or explosion. Use non-sparking tools. Do not cut, grind, drill, weld, or reuse containers unless adequate precautions are taken against these hazards. In case of spill, eliminate and/or shut off ignition sources. Take immediate steps to stop and contain release. Dike if necessary. When cool, scrape up material for disposal. For spills on water, consult with local, state, and regional authorities for approved clean up procedures.